





CULTURA PLUS



Cultura Plus was our first recessed office luminaire, and remains the flagship. The light source is setback in the fixture to reduce glare and create a beautiful aesthetic. A high performance microprismatic diffuser allows us to not just illuminate horizontal surfaces, but vertical surfaces and faces too. A 3 x 2 LED board configuration ensures that the diffuser is homogenous and allows us to offer performance circadian options.

EFFICACY

114.7 lm/W

TYPICAL POWER DENSITY

3.49 W/m²

TYPICAL UGR (large open office)

19

TYPICAL UGR (small office)

19

TYPICAL VERTICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 171 lx

TYPICAL CYLINDRICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 167 lx

TYPICAL FACIAL MODELLING RATIO

0.489

TYPICAL CEILING ILLUMINANCE (as % of working plane)

20.2 %

TYPICAL WALL ILLUMINANCE (as % of working plane)

54.2 %

WELL



GREENSTAR



Download general data sheet 

Download IES files 

CULTURA SOFT FLAT



Cultura Soft Flat is the all rounder. It's efficient, low glare, adaptable to a range of different spacings, and has a great aesthetic.

EFFICACY

93 lm/W

TYPICAL POWER DENSITY

4.42 W/m²

TYPICAL UGR (large open office)

19

TYPICAL UGR (small office)

19

TYPICAL VERTICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 176

TYPICAL CYLINDRICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 175

TYPICAL FACIAL MODELLING RATIO

0.501

TYPICAL CEILING ILLUMINANCE (as % of working plane)

20.3 %

TYPICAL WALL ILLUMINANCE (as % of working plane)

54.9 %

WELL



GREENSTAR



Download general data sheet 

Download IES files 

CULTURA SOFT CURVED

To create brighter spaces, we need more light on vertical surfaces. The rounded diffuser pushes more light out laterally resulting in brighter walls, happier faces and improved uniformity on task areas.

EFFICACY

104 lm/W

TYPICAL POWER DENSITY

3.97 W/m²

TYPICAL UGR (large open office)

22

TYPICAL UGR (small office)

19

TYPICAL VERTICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 182

TYPICAL CYLINDRICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 185

TYPICAL FACIAL MODELLING RATIO

0.525

TYPICAL CEILING ILLUMINANCE (as % of working plane)

20.9 %

TYPICAL WALL ILLUMINANCE (as % of working plane)

61.5 %

WELL



GREENSTAR



[Download general data sheet](#) 

[Download IES files](#) 

CULTURA VC



The Cultura VC was designed for a specific purpose - Video Conferencing.

The challenge with Video Conferencing lighting is achieving sufficient vertical illuminance on the occupants faces without causing excessive glare. Often a pendant luminaire is required to achieve adequate light levels, but the Cultura VC can get you there with a standard recessed layout.

EFFICACY

123 lm/W

TYPICAL POWER DENSITY

7.82 W/m²

TYPICAL UGR (for seated meeting positions)

10

TYPICAL VERTICAL ILLUMINANCE (for seated meeting positions)

Avg 411 lx

TYPICAL CYLINDRICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 281 lx

TYPICAL FACIAL MODELLING RATIO

0.42

TYPICAL CEILING ILLUMINANCE (as % of working plane)

17.6%

TYPICAL WALL ILLUMINANCE (as % of working plane)

43.2%

NOTE: Calculations based on typical 6 m x 4 m boardroom layout.

[Download general data sheet](#) 

[Download IES files](#) 

CULTURA BASE



The Cultura Base was designed for Base Build projects, with less features and a lower price. We haven't sacrificed on quality though - the Cultura base uses the same high quality LED boards, drivers, and diffuser as its Cultura siblings.

EFFICACY

112 lm/W

TYPICAL POWER DENSITY

3.65 W/m²

TYPICAL UGR (large open office)

22

TYPICAL UGR (small office)

19

TYPICAL VERTICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 175 lx

TYPICAL CYLINDRICAL ILLUMINANCE (for seated workers at 1.2m)

Avg 172 lx

TYPICAL FACIAL MODELLING RATIO

0.497

TYPICAL CEILING ILLUMINANCE (as % of working plane)

20.6 %

TYPICAL WALL ILLUMINANCE (as % of working plane)

57.3 %

WELL



GREENSTAR



Download general data sheet 

Download IES files 

DEFINITIONS



	PLUS (2500 lm) 2.4 m x 2.7 m	SOFT FLAT (2570 lm) 2.4 m x 2.7 m	SOFT CURVE (2575 lm) 2.4 m x 2.7 m	BASE (2550 lm) 2.4 m x 2.7 m
EFFICACY	114.7 lm/W	93 lm/W	104 lm/W	112 lm/W
TYPICAL POWER DENSITY	3.49 W/m ²	4.42 W/m ²	3.97 W/m ²	3.65 W/m ²
TYPICAL UGR (large open office)	Max 19	Max 19	Max 22	Max 22
TYPICAL UGR (small office)	2250 lm output: Max 19	2360 lm output: Max 19	2360 lm output: Max 19	2340 lm output: Max 19
TYPICAL VERTICAL ILLUMINANCE (for seated workers at 1.2m)	Avg 171 lx	Avg 176	Avg 182	Avg 175 lx
TYPICAL CYLINDRICAL ILLUMINANCE (for seated workers at 1.2m)	Avg 167 lx	Avg 175	Avg 185	Avg 172 lx
TYPICAL FACIAL MODELLING RATIO	0.489	0.501	0.525	0.497
TYPICAL CEILING ILLUMINANCE (as % of working plane)	20.2%	20.3%	20.9%	20.6%
TYPICAL WALL ILLUMINANCE (as % of working plane)	54.2%	54.9%	61.5%	57.3%

EFFICACY

A measure of a luminaire's efficiency to produce light from power.

POWER DENSITY

The amount of power used to illuminate 1m² to an appropriate level (in offices 320lx average).

TYPICAL UGR

Unified Glare Ratio or UGR is a metric relating to the glare experienced by users in continually occupied spaces. Higher values relate to higher glare.

VERTICAL ILLUMINANCE

The amount of light hitting a vertical plane at 1.2m (typical seated eye height). This metric is useful for assessing facial illumination and Equivalent Melanopic Lux for the Well Building Standard.

CYLINDRICAL ILLUMINANCE

A measure of a luminaire's efficiency to produce light from power.

FACIAL MODELLING RATIO

The ratio of between the cylindrical illuminance and horizontal illuminance for worker locations at seated eye height. The modelling ratio indicates how strongly a person's features will be 'modelled' by the light source and values between 0.3 (stronger shadows) and 0.6 (flatter shadows) are recommended.

CEILING ILLUMINANCE (AS % OF WORKING PLANE)

Useful for indicating how 'bright' the ceiling will appear compared with the horizontal surfaces. 30 - 90% is considered good practice.

WALL ILLUMINANCE (AS % OF WORKING PLANE)

Useful for indicating how 'bright' the wall will appear compared with the horizontal surfaces. 50 - 80% is considered good practice.

WELL & GREEN STAR STANDARDS

