









DESCRIPTION

Angle Andy 25 was conceived as a multi-functional profile with a 45° asymmetric light distribution. Application possibilities include joinery such as under cabinet or retail displays, glass cabinets such as jewellery displays, surface mounted wall washing, suspended wall washing and exterior applications when used with IP65 LED strip.

FEATURES

- Made locally and factory assembled
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- Polycarbonate diffuser UV resistant
- Max 20 W per metre

TECHNICAL DATA

APPLICATIONS	Task lighting in kitchen cabinetry, lighting for shelving or display units, hallway lighting, wall-washing						
INSTALLATION	LATION Interior Exterior (with IP65 LED strip)						
MOUNTING	TING Surface mounted Rod suspended						
MATERIALS	Extruded aluminium body Polycarbonate diffuser AES plastic end caps						
LIGHT SOURCE	LED ribbon strip						
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W						
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available						
WARRANTY	7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details						
FINISH	White Black Satin Anodised *Custom colours available						





















LED STRIP

PRO Series IP20 & IP65

	6 W/m			12 W/m 18 W			18 W/m	18 W/m 30 V			N/m - IP20 only	
	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
ľ	237 lm	237 lm	256 lm	493 lm	493 lm	529 lm	730 lm	776 lm	785 lm	-	-	-

RGBW IP20 & IP65

22 W/m						
RED	GREEN	BLUE	3000K			
47 lm	126 lm	31 lm	183 lm			

The above outputs are quoting luminaire output lumens per metre 30 W/m strip only available in IP20.

IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating. Electrical and optical data variance +/- 10%

ACCESSORIES



JMC-12 Joinery mounting clip



JN-ST-12 Straight joiner



JN-90-12 90 degree joiner



JN-120-12 120 degree joiner



JN-135-12 135 degree joiner



SRK-1-S | SRK-1-W Rod suspension kit (Rod not included)



SRK-6-S | SRK-W Rod suspension kit (Rod not included)



| ROD-2M Suspension rod -0.5m | 1m | 2m

