



## DESCRIPTION

The Bob Each Way 65 profile is a compact uplight/downlight solution. A versatile system suitable for various mounting options, Bob Each Way 65 can be surface mounted, wall mounted and suspended. Both wire and rod suspension options are available for the Bob Each Way 65 profile.

## FEATURES

- Made locally and factory assembled
- Indirect | direct option
- Polycarbonate diffuser – UV resistant

## TECHNICAL DATA

APPLICATIONS	Task lighting over kitchen islands or reception counters, mirror lighting
INSTALLATION	Interior   Exterior (with IP65 LED strip)
MOUNTING	Surface mounted   Rod suspended   Wire suspended   Wall mounted
MATERIALS	Extruded aluminium body   Polycarbonate diffuser   Aluminium end caps
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available (independant optional)
WARRANTY	7 year product warranty   13 months labour warranty. Refer to <a href="http://www.lightculture.com.au">www.lightculture.com.au</a> for more details
LIGHT SOURCE	LED ribbon strip
SDCM*	2-step MacAdam
CRI*	≥ 95
R9*	80+
SOURCE LIFE*	L80 B10=82 000 hrs

FINISH

White

Black

Satin Anodised

Custom colours available

\* Figures for the PRO Series LED Strips



## LED STRIP LUMEN PACKAGES

INDIRECT (UP)				DIRECT (DOWN)			
PRO Series IP20 & IP65	6 W/m	2700 K	564 lm	PRO Series IP20 & IP65	6 W/m	2700 K	273 lm
		3000 K	564 lm			3000 K	273 lm
		4000 K	608 lm			4000 K	294 lm
	12 W/m	2700 K	1172 lm		12 W/m	2700 K	567 lm
		3000 K	1172 lm			3000 K	567 lm
		4000 K	1259 lm			4000 K	609 lm
	18 W/m	2700 K	1736 lm		18 W/m	2700 K	840 lm
		3000 K	1845 lm			3000 K	893 lm
		4000 K	1866 lm			4000 K	903 lm
	30 W/m IP20 ONLY	2700 K	2821 lm		30 W/m IP20 ONLY	2700 K	1365 lm
		3000 K	2864 lm			3000 K	1386 lm
		4000 K	2908 lm			4000 K	1407 lm
RGBW IP20 & IP65	22 W/m	RED	113 lm	RGBW IP20 & IP65	22 W/m	RED	55 lm
		GREEN	299 lm			GREEN	145 lm
		BLUE	74 lm			BLUE	36 lm
		3000 K	463 lm			3000 K	211 lm

The above outputs are quoting luminaire output lumens per metre  
 30 W/m strip only available in IP20.  
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.  
 Electrical and optical data variance +/- 10%

## SPECIFYING CODE

PROFILE	MOUNTING	LENGTH	FINISH	INDIRECT LUMEN PACKAGE	DIRECT LUMEN PACKAGE	IP RATING	CONTROL
BEW65	Surface Mounted		White			IP20	Non Dim
	Wall Mounted	Length mm	Black	Refer to Lumen packages above	Refer to Lumen packages above	IP65	DALI
	Rod Suspended		Satin Anodised				Phase Cut
	Wire Suspended		Custom				Independent <small>Optional Addition</small>

Example:

BEW65	Wire Suspended	2000mm	Black	6W 3000K	30W 3000K	IP20	DALI Independent
-------	----------------	--------	-------	----------	-----------	------	------------------

## ACCESSORIES

JN-ST-6 Straight joiner	JN-90-6 90 degree joiner	JN-LOC Joiner locator	CB-BEW-60-R-S   CB-BEW-60-R-W Cable base 60, recessed	CB-BEW-80-SM-S   CB-BEW-80-SM-W Cable base 80, surface-mounted	SWK-5-2M   SWK- 5-4M Wire suspension	SRK-5-S   SRK-5-W Rod suspension kit (Rod not included)
SRK-10-S   SRK-10-W Rod suspension kit (Rod not included)	ROD-0.5M   ROD-1M   ROD-2M Suspension rod - 0.5m   1m   2m	WB-BEW Wall bracket				

