

## DESCRIPTION

The Downhill Dan 14 extrusion is a compact solution providing dot-free lighting. A versatile system suitable for various mounting options, Downhill Dan 14 can be surface mounted, recessed and suspended. Both wire and rod suspension options are available for the Downhill Dan 14 extrusion and the recessing system for plasterboard ceilings and walls, creates a perfect trimless recessed finish every time.

## FEATURES

- Made locally and factory assembled
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- Polycarbonate diffuser - UV resistant
- Straight joiners and L-plates
- Max. 14 W recessed | 20 W surface-mounted

## TECHNICAL DATA

APPLICATIONS	Task lighting in kitchen cabinetry, shelving or display units, hallways
INSTALLATION	Interior   Exterior (with IP65 LED strip)
MOUNTING	Surface mounted   Recessed   Rod suspended   Wire suspended
MATERIALS	Extruded aluminium body   Polycarbonate diffuser   AES plastic end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty   13 months labour warranty. Refer to <a href="http://www.lightculture.com.au">www.lightculture.com.au</a> for more details

## FINISH



\*Custom colours available



## LED STRIP

### PRO Series IP20 & IP65


6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
289 lm	289 lm	312 lm	601 lm	601 lm	645 lm	890 lm	946 lm	957 lm	-	-	-

### RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
58 lm	154 lm	38 lm	223 lm

The above outputs are quoting luminaire output lumens per metre  
 30 W/m strip only available in IP20.  
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.  
 Electrical and optical data variance +/- 10%

## ACCESSORIES



JMC-12  
Joinery mounting clip




JN-ST  
Straight joiner



JN-90  
90 degree joiner



CB-60-R-S |  
CB-60-R-W  
Cable base 60,  
recessed



CB-80-SM-S |  
CB-80-SM-W  
Cable base 80,  
surface-mounted



SWK-1-2M | SWK-  
1-4M  
Wire suspension



SRK-1-S | SRK-1-W  
Rod suspension kit  
(Rod not included)



SRK-6-S | SRK-6-W  
Rod suspension kit  
(Rod not included)



ROD-0.5M | ROD-1M  
| ROD-2M  
Suspension rod -  
0.5m | 1m | 2m



MB-ADJ  
Adjustable mounting  
bracket

