




## DESCRIPTION

The Downhill Dan 30 extrusion is a versatile and powerful downlighting system. Utilizing up to a 30W per metre LED strip, the profile is ideal for applications where maximum light output is key. A versatile system suitable for various mounting options, Downhill Dan 30 can be surface mounted, recessed and suspended. Both wire and rod suspension options are available and the cowling accessory for plastered ceilings and walls creates a beautiful trimless finish.

## FEATURES

- Made locally and factory assembled
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- PMMA diffuser - scratch and mark resistant
- Max. 30 W per metre

## TECHNICAL DATA

APPLICATIONS	General downlighting in kitchens, living rooms, dining rooms, reception counters
INSTALLATION	Interior   Exterior (with IP65 LED strip)
MOUNTING	Surface mounted   Recessed   Rod suspended   Wire suspended
MATERIALS	Extruded aluminium body   PMMA diffuser   Aluminium end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty   13 months labour warranty. Refer to <a href="http://www.lightculture.com.au">www.lightculture.com.au</a> for more details
FINISH	   *Custom colours available



## LED STRIP

### PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
277 lm	277 lm	298 lm	574 lm	574 lm	617 lm	851 lm	904 lm	915 lm	1383 lm	1404 lm	1425 lm

### RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
55 lm	147 lm	36 lm	214 lm

The above outputs are quoting luminaire output lumens per metre  
 30 W/m strip only available in IP20.  
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.  
 Electrical and optical data variance +/- 10%

## ACCESSORIES



MC-30  
Mounting clip



JN-ST-12  
Straight joiner



JN-90-12  
90 degree joiner



CB-60-R-S |  
CB-60-R-W  
Cable base 60,  
recessed



CB-80-SM-S |  
CB-80-SM-W  
Cable base 80,  
surface-mounted



SWK-1-2M | SWK-  
1-4M  
Wire suspension



SRK-1-S | SRK-1-W  
Rod suspension kit  
(Rod not included)




SRK-6-S | SRK-6-W  
Rod suspension kit  
(Rod not included)



ROD-0.5M | ROD-1M  
| ROD-2M  
Suspension rod -  
0.5m | 1m | 2m



C-30-I  
Recessing cowling



C-DD22-EC-I  
Recessing cowling  
end cap



WB-DD30  
Wall bracket



JN-120-12  
120 degree joiner



JN-135-12  
135 degree joiner



### 1.4 Share of Voice (Fixed - Non-brand Keywords)

Full Advertiser by State  
Company: Apple vs. Competitor: Samsung  
Keywords: iPhone vs. Samsung  
2018-2019 - 2019-2020

