

## FLAT FREDDIE 14







## **DESCRIPTION**

Much like its close cousin, Downhill Dan 14, Flat Freddie 14 is a compact solution providing "dotfree" lighting. A versatile system suitable for various mounting options, Flat Freddie 14 can be surface mounted, recessed or suspended. Both wire and rod suspension options are available and a simple method of recessing into plasterboard ceilings provides a clean, trimless look.

## **FEATURES**

- Made locally and factory assembled
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment •
  - Polycarbonate diffuser UV resistant
- Max 20 W per metre .

## **TECHNICAL DATA**

APPLICATIONS	Task lighting in kitchen cabinery, shelving or display units, hallways					
INSTALLATION	Interior   Exterior (with IP65 LED strip)					
MOUNTING	Recessed   Surface mounted   Rod suspended   Wire suspended					
MATERIALS	Extruded aluminium body   Polycarbonate diffuser   AES plastic end caps					
LIGHT SOURCE	LED ribbon strip					
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W					
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available					
WARRANTY	7 year product warranty   13 months labour warranty. Refer to <u>www.lightculture.com.au</u> for more details					
FINISH	White Black Satin Anodised *Custom colours available					





# FLAT FREDDIE 14

### LED STRIP

### PRO Series IP20 & IP65

6 W/m			12 W/m 18 W			18 W/m	W/m 30 W/m - IP20 only			only	
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
294 lm	294 lm	316 lm	610 lm	610 lm	655 lm	904 lm	961 lm	972 lm	-	-	-

The above outputs are quoting luminaire output lumens per metre

30 W/m strip only available in IP20.

IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating. Electrical and optical data variance +/- 10%

## ACCESSORIES



Joinery mounting clip

SRK-6-S | SRK-6-W

Rod suspension kit (Rod not included)

JMC-12



iner 9



MB-ADJ Adjustable mounting bracket



JN-90-12

MB-ADJ Adjustable mounting bracket



CB-80-SM-S | CB-80-SM-W Cable base 80, surface-mounted



C-FF14-1 Recessing cowling



CB-80-SM-S | CB-80-SM-W Cable base 80, surface-mounted



C-FF14-EC-1 Recessing cowling end cap

#### **RGBW IP20 & IP65**

22 W/m								
RED	GREEN	BLUE	3000K					
59 lm	156 lm	38 lm	227 lm					



SWK-1-2M | SWK-

1-4M

Wire suspension

SRK-1-S | SRK-1-W Rod suspension kit (Rod not included)



