

DESCRIPTION

Flat Freddie 35 is a versatile profile suitable for a huge range of applications. Flat Freddie 35 offers a unique combination of a powerful white light with an independent RGB light - great for residential or hospitality applications.

FEATURES

- Made locally and factory assembled
- Dot-free and uniform lighting
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- Max. 30 W per metre

TECHNICAL DATA

APPLICATIONS	Bars, restaurants, kitchens, living rooms, dining rooms, reception counters, lobbies
INSTALLATION	Interior Exterior (with IP65 LED strip)
MOUNTING	Surface mounted Recessed Rod suspended Wire suspended
MATERIALS	Extruded aluminium body PMMA diffuser Aluminium end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details

FINISH



*Custom colours available



LED STRIP

PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
314 lm	314 lm	338 lm	652 lm	652 lm	700 lm	966 lm	1026 lm	1038 lm	1570 lm	1594 lm	1618 lm

RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
63 lm	167 lm	41 lm	242 lm

The above outputs are quoting luminaire output lumens per metre
 30 W/m strip only available in IP20.
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.
 Electrical and optical data variance +/- 10%

ACCESSORIES



JN-ST-23
Straight joiner, top
extrusion



JN-ST-21
Pair of straight
joiners, for sides of
extrusion



JN-90-23
90 degree joiner, top
of extrusion



JN-90-21
Pair of 90 degree
joiners, for sides of
extrusion



CB-60-R-S |
CB-60-R-W | CB-
60-R-B
Cable base 60, recessed



CB-80-SM-S |
CB-80-SM-W | CB-80-
SM-B
Cable base 80,
surface-mount



SWK22-1-1M |
SWK22-1-2M |
SWK22-1-4M
Wire suspension - 1m,
2m, 4m




SRK-11-S | SRK-11-W |
SRK-11-B
Rod suspension kit
(Rod not included)



SRK-12-S | SRK-12-W
| SRK-12-B
Rod suspension kit
(Rod not included)



ROD-0.5M | ROD-1M
| ROD-2M
Suspension rod -
0.5m | 1m | 2m



C-FF35-1
Recessing cowling



C-FF35-EC-1
Recessing cowling

