




DESCRIPTION

The Sideways Sally 20C extrusion is a compact uplight/downlight solution providing powerful LED lighting. A versatile system suitable for various mounting options, Sideways Sally 20C can be surface mounted, wall mounted and suspended. The concealed mounting clip provides a quick and secure fixing to joinery. Both wire and rod suspension options are available for the Sideways Sally 20C extrusion.

FEATURES

- Made locally and factory assembled
- Indirect | direct option
- Dot-free and uniform lighting
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- PMMA diffuser - scratch and mark resistant
- Max. 14 W upward, 20 W downward

TECHNICAL DATA

APPLICATIONS	Task lighting over kitchen islands or reception counters, mirror lighting
INSTALLATION	Interior Exterior (with IP65 LED strip)
MOUNTING	Surface mounted Rod suspended Wire suspended Wall mounted
MATERIALS	Extruded aluminium body PMMA diffuser Aluminium end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details
FINISH	   *Custom colours available



LED STRIP

PRO Series IP20 & IP65


6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
488 lm	488 lm	525 lm	1013 lm	1013 lm	1088 lm	1500 lm	1594 lm	1613 lm	-	-	-

RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
98 lm	259 lm	64 lm	377 lm

The above outputs are quoting luminaire output lumens per metre
 30 W/m strip only available in IP20.
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.
 Electrical and optical data variance +/- 10%

ACCESSORIES



JMC-12
Joinery mounting clip



JN-ST-12
Straight joiner



JN-90-12
90 degree joiner



CB-60-R-S / CB-60-R-W /
CB-60-R-B
Cable base 60,
recessed



CB-80-SM-S / CB-80-SM-W /
CB-80-SM-B
Cable base 80,
surface mount



SWK-1-1M / SWK-1-2M /
SWK-1-4M
Wire suspension



SRK-1-S / SRK-1-W /
SRK-1-B
Rod suspension kit
(rod not incl.)



SRK-6-S / SRK-6-W /
SRK-6-B
Rod suspension kit
(rod not incl.)



ROD-0.5M | ROD-1M |
ROD-2M
Suspension rod -
0.5m | 1m | 2m



WB-SS20
Wall bracket



JN-120-12
120 degree joiner



JN-135-12
135 degree joiner

The Woolstore Management Ltd
GS1 New Zealand Inc
ABC Business Sales
Heart Foundation

