

DESCRIPTION

Sideways Sally 5C has many uses as a surface mounted profile solution, whether it is used as a slim-line mirror light in a bathroom, discrete task lighting under a shelf or tucked into a pelmet. It can even be suspended on wire or rod suspensions as a super-slim pendant light. With diffuser options of both curved and rectangular, this profile is sure to be a great addition to any specifier's tool kit.

FEATURES

- Made locally and factory assembled
- Dot-free and uniform lighting
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- PMMA diffuser - scratch and mark resistant
- Max. 20 W per metre

TECHNICAL DATA

APPLICATIONS	Mirror lighting, kitchen joinery, display shelving
INSTALLATION	Interior Exterior (with IP65 LED strip)
MOUNTING	Surface mounted Rod suspended Wire suspended
MATERIALS	Extruded aluminium body PMMA diffuser AES plastic end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details

FINISH



*Custom colours available



LED STRIP

PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
488 lm	488 lm	525 lm	1013 lm	1013 lm	1088 lm	1500 lm	1594 lm	1613 lm	-	-	-

RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
98 lm	259 lm	64 lm	377 lm

The above outputs are quoting luminaire output lumens per metre
 30 W/m strip only available in IP20.
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.
 Electrical and optical data variance +/- 10%

ACCESSORIES




JMC-12
Joinery mounting clip



JN-ST
Straight joiner



JN-90
90 degree joiner



MB-ADJ
Adjustable mounting
bracket

