

DESCRIPTION

Sideways Sally 5R has many uses as a surface mounted profile solution, whether it is used as a slim-line mirror light in a bathroom, discrete task lighting under a shelf or tucked into a pelmet. It can even be suspended on wire or rod suspensions as a super-slim pendant light. With diffuser options of both curved and rectangular, this profile is sure to be a great addition to any specifier's tool kit.

FEATURES

- Made locally and factory assembled
- Dot-free and uniform lighting
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- PMMA diffuser - scratch and mark resistant
- Max. 20 W per metre

TECHNICAL DATA

| | |
|--------------|---|
| APPLICATIONS | Mirror lighting, kitchen joinery, display shelving |
| INSTALLATION | Interior Exterior (with IP65 LED strip) |
| MOUNTING | Surface mounted Rod suspended Wire suspended |
| MATERIALS | Extruded aluminium body PMMA diffuser AES plastic end caps |
| LIGHT SOURCE | LED ribbon strip |
| POWER SUPPLY | 24V DC - remote driver options ranging from 6 W up to 320 W |
| DIMMABLE | DALI, 1-10V, Phase Cut and Bluetooth drivers available |
| WARRANTY | 7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details |
| FINISH | White Black Satin Anodised <i>*Custom colours available</i> |



LED STRIP

PRO Series IP20 & IP65

| 6 W/m | | | 12 W/m | | | 18 W/m | | | 30 W/m - IP20 only | | |
|--------|--------|--------|---------|---------|---------|---------|---------|---------|--------------------|--------|--------|
| 2700 K | 3000 K | 4000 K | 2700 K | 3000 K | 4000 K | 2700 K | 3000 K | 4000 K | 2700 K | 3000 K | 4000 K |
| 495 lm | 495 lm | 533 lm | 1029 lm | 1029 lm | 1105 lm | 1524 lm | 1619 lm | 1638 lm | - | - | - |

RGBW IP20 & IP65

| 22 W/m | | | |
|--------|--------|-------|--------|
| RED | GREEN | BLUE | 3000K |
| 99 lm | 263 lm | 65 lm | 383 lm |

The above outputs are quoting luminaire output lumens per metre
 30 W/m strip only available in IP20.
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.
 Electrical and optical data variance +/- 10%

ACCESSORIES




JMC-12
Joinery mounting clip



JN-ST
Straight joiner



JN-90
90 degree joiner



MB-ADJ
Adjustable mounting bracket

