


DESCRIPTION




Sonny Side Up 22 is a purpose-designed powerful uplight profile. Don't be fooled by its petite size as it packs a mighty punch of light up. Both wire and rod suspensions are available for the Sonny Side Up 22 extrusion.



FEATURES

- Made locally and factory assembled
- Unique mounting clip design for easy installation
- Clear diffuser - scratch and mark resistant
- Max. 40 W per metre

TECHNICAL DATA

APPLICATIONS	Reception counters, meeting rooms, commercial offices
INSTALLATION	Interior
MOUNTING	Rod suspended Wire suspended
MATERIALS	Extruded aluminium body Polycarbonate diffuser Aluminium end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details
FINISH	   *Custom colours available



LED STRIP

PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
439 lm	439 lm	473 lm	913 lm	913 lm	980 lm	1352 lm	1437 lm	1453 lm	2197 lm	2231 lm	2265 lm

RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
88 lm	233 lm	57 lm	339 lm

The above outputs are quoting luminaire output lumens per metre
 30 W/m strip only available in IP20.
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.
 Electrical and optical data variance +/- 10%


ACCESSORIES



JN-ST-18
Straight joiner



JN-90-18
90 degree joiner



CB-SSU22-60-R-S |
CB-SSU22-60-R-W
Cable base 60,
recessed



CB-SSU22-80-SM-S |
CB-SSU22-80-SM-W
Cable base 80,
surface-mounted



SWK-4-2M | SWK-
4-4M
Wire suspension



SRK-4-S | SRK-4-W
Rod suspension kit
(Rod not included)



SRK-9-S | SRK-9-W
Rod suspension kit
(Rod not included)



ROD-0.5M | ROD-1M
| ROD-2M
Suspension rod -
0.5m | 1m | 2m

