



## DESCRIPTION

Trim Tim 13 has similar dimensions and features to Downhill Dan 14, including the added feature of recessing trims to cover the cut edges of joinery or plasterboard when recessing. Also featured are small ribs either side of the profile which allow Trim Tim 13 to be friction-fitted into an 18mm routed slot in joinery without the need for screws. The 13mm depth provides "dot-free" lighting in building materials as thin as 18mm.

## FEATURES

- Made locally and factory assembled
- V-groove for accurate drilling and strip alignment
- Polycarbonate diffuser – UV resistant
- Dot-free and uniform lighting
- Max. 20 W per metre

## TECHNICAL DATA

APPLICATIONS	Task lighting in kitchen cabinetry, lighting for shelving or display units
INSTALLATION	Interior   Exterior (with IP65 LED strip)
MOUNTING	Recessed
MATERIALS	Extruded aluminium body   Polycarbonate diffuser   AES plastic end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty   13 months labour warranty. Refer to <a href="http://www.lightculture.com.au">www.lightculture.com.au</a> for more details

## FINISH



White



Black



Satin Anodised

\*Custom colours available



## LED STRIP

### PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
289 lm	289 lm	312 lm	601 lm	601 lm	645 lm	890 lm	946 lm	957 lm	-	-	-

### RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
58 lm	154 lm	38 lm	223 lm

The above outputs are quoting luminaire output lumens per metre  
 30 W/m strip only available in IP20.  
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.  
 Electrical and optical data variance +/- 10%

## ACCESSORIES



JN-ST  
Straight joiner



JN-90  
90 degree joiner

