



DESCRIPTION

Trimless Tim 15 is designed to recess seamlessly into joinery to offer dot-free lighting solutions. The small ribs either side of the profile allow Trimless Tim 15 to be friction-fitted into an 18mm routed slot in joinery without the need for screws. The flat diffuser provides an excellent, flush, high-level finish to the installation.

FEATURES

- Made locally and factory assembled
- V-groove for accurate drilling and strip alignment
- Flat and discrete diffuser
- Polycarbonate diffuser - UV resistant
- Max. 20 W per metre

TECHNICAL DATA

APPLICATIONS	Task lighting in kitchen cabinetry, lighting for shelving or display units
INSTALLATION	Interior Exterior (with IP65 LED strip)
MOUNTING	Recessed
MATERIALS	Extruded aluminium body Polycarbonate diffuser AES plastic end caps
LIGHT SOURCE	LED ribbon strip
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty 13 months labour warranty. Refer to www.lightculture.com.au for more details

FINISH



*Custom colours available



LED STRIP

PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
294 lm	294 lm	316 lm	610 lm	610 lm	655 lm	904 lm	961 lm	972 lm	-	-	-

RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
59 lm	156 lm	38 lm	227 lm

The above outputs are quoting luminaire output lumens per metre
 30 W/m strip only available in IP20.
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.
 Electrical and optical data variance +/- 10%

ACCESSORIES



JN-ST
Straight joiner



JN-90
90 degree joiner



love your work

303

VIDAK

CANVAS

VIDAK