





NEON CRYSTAL | RGBW



COLOUR	CODE
--------	------

RGBW	BL-LS-5150
------	------------

ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%
SOLD BY THE METRE
IES FILES AVAILABLE



TECHNICAL DATA

LED WATTS	15 W/m	LED PITCH	16.7 mm	CUTTING LENGTH	100 mm
INPUT VOLTS	24 V DC constant voltage	LED QTY	60	HOUSING	UV and flame resistant clear PVC
OPERATING TEMP	- 20 °C ~ + 45 °C	SOURCE LIFE	50,000 hrs	CONTROL	Requires 4-channel controller
COLOUR	R 615-625 nm G 520-530 nm B 465-475 nm W 3000 K +/- 175 K	WARRANTY	5 years	MAX. RUN PER FEED	5m using one feed 10m using two feeds
LUMENS	R ≥ 85 lm/m G ≥ 230 lm/m B ≥ 40 lm/m W ≥ 230 lm/m	MIN BEND RADIUS	25 mm	MOUNTING	See Installation Guide for mounting accessories
BEAM ANGLE	120°	BEND DIRECTION	Vertical bending		
		DIMENSIONS	15.5 mm x 6 mm		
		INGRESS PROTECTION	IP65 Protection established by use of connection type See Installation Guide for connections		

APPLICATION

- Dynamic colour installations that chase, blend, flow, flash, skip, or fade
- Theatres, bars, restaurants, retail
- Cove lighting
- Architectural features
- Exterior or interior installations
- Swimming or feature pools

FEATURES

- A clear PVC allows maximum light output
- UV and flame resistant
- Suitable for use around salt or chlorinated water