




## NEON CRYSTAL | TUNEABLE WHITE



COLOUR	CODE
--------	------

2700 K - 6000 K TUNEABLE	BL-LS-5050
-----------------------------	------------

ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%  
SOLD BY THE METRE  
IES FILES AVAILABLE



### TECHNICAL DATA

LED WATTS	12 W/m	LED QTY	144	CUTTING LENGTH	83.3 mm
INPUT VOLTS	24 V DC constant voltage	SOURCE LIFE	50,000 hrs	HOUSING	UV and flame resistant clear PVC
CRI	≥ 80	WARRANTY	5 years	CONTROL	Requires 2-channel controller
OPERATING TEMP	- 20 °C ~ + 45 °C	MIN BEND RADIUS	25 mm	MAX. RUN PER FEED	10 m using one feed 20 m using two feeds
COLOUR	WW 2725 K ±145K CW 6000 K ±355K	BEND DIRECTION	Vertical bending	MOUNTING	See Installation Guide for mounting accessories
LUMENS	WW ≥ 350 lm/m CW ≥ 350 lm/m	DIMENSIONS	15.5 mm x 6 mm		
BEAM ANGLE	120°	INGRESS PROTECTION	IP65 or IP67 Protection established by use of connection type See Installation Guide for connections		
LED PITCH	13.8 mm				

### APPLICATION

- Ideal for applications where colour temperature adjustment is required
- Cove lighting, handrails, or toekicks
- Architectural features
- Exterior or interior installations
- Swimming or feature pools

### FEATURES

- A clear PVC allows maximum light output
- UV and flame resistant
- Suitable for use around salt or chlorinated water