





# NEON EDGE | RGBW



COLOUR	CODE
--------	------

RGBW	BL-LS-4150-RGBW
------	-----------------

ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%  
SOLD BY THE METRE  
IES FILES AVAILABLE



## TECHNICAL DATA

LED WATTS	15 W/m	BEAM ANGLE	160°	CUTTING LENGTH	100 mm
INPUT VOLTS	24 V DC constant voltage	SOURCE LIFE	50,000 hrs	HOUSING	UV and flame resistant white PVC
OPERATING TEMP	- 20 °C ~ + 45 °C	WARRANTY	5 years	CONTROL	Requires 4-channel controller
COLOUR	R 615 - 625 nm G 520 - 530 nm B 465 - 475 nm W 3000 K +/- 175 K	MIN BEND RADIUS	60 mm	MAX. RUN PER FEED	5 m using one feed 10 m using two feeds
LUMENS	R ≥ 40 lm/m G ≥ 100 lm/m B ≥ 15 lm/m W ≥ 100 lm/m	DIMENSIONS	11.5 mm x 21 mm	MOUNTING	See Installation Guide for mounting accessories
		BEND DIRECTION	Horizontal bending		
		INGRESS PROTECTION	IP67 or IP68 Protection established by use of connection type See Installation Guide for connections		

## APPLICATION

- Creative colour installations. Softer colours to pastels.
- Theatres, bars, restaurants, retail
- Cove lighting, handrails or toekicks
- Architectural features
- Exterior or interior installations
- Swimming or feature pools

## FEATURES

- UV and flame resistant
- Suitable for use around salt or chlorinated water