


NEON X | 15W/M | TUNEABLE WHITE



CODE: NEON-X-15W-TW-22-57

White range 22-57 / 27-57 or 30-57





COLOUR	LUMENS
2200K + 5700K	210lm/m + 240lm/m
<i>ELECTRICAL &amp; OPTICAL DATA VARIANCE +/- 10% SOLD BY THE METRE IES FILES AVAILABLE</i>	

APPLICATIONS

- Ideal for applications where colour temperature adjustment is required
- Signage & cove lighting
- Architectural features
- Exterior or interior installations
- Swimming or feature pools

FEATURES

- UV & flame resistant
- Suitable for use around salt or chlorinated water



LED WATTS	15W/m
INPUT VOLTS	24V DC Constant Voltage
OPERATING TEMP.	-25°C ~ +50°C
MAX. RUN PER POWER FEED	10m using one feed 20m using two feeds

CRI	≥80
WHITE CHIP COLOUR	2200K+5700K as standard 2700K+5700K or 3000K+5700K Available on request
BEAM ANGLE	120°
LED TYPE	Epistar SMD LED 2835
LED QTY	120 LED/m
SOURCE LIFE	50,000 hours
WARRANTY	5 years

DIMENSIONS	W11.5 × H21mm
BEND DIRECTION	Horizontal bending
CUTTING LENGTH	100mm
MINIMUM BEND RADIUS	40mm
HOUSING	UV & flame resistant white PVC
INGRESS PROTECTION	IP67 Snap Connector or IP68 Injection Moulding <i>Protection established by use of connection type</i>
CONTROL	Requires 2-channel controller
MOUNTING	Profile and clips available

NEON X | 15W/M | TUNEABLE WHITE | CONNECTION DIAGRAMS

