

NEON Y3 | 13W/M | RGB



CODE: NEON Y3-13W-RGB

COLOUR	LUMENS
RED	83lm/m
GREEN	245lm/m
BLUE	46lm/m
RGB (WHITE)	350lm/m



ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%
SOLD BY THE METRE
IES FILES AVAILABLE

APPLICATIONS

- Creative colour installations. Theatres, bars, restaurants, and retail
- Cove lighting, handrails, or toe-kicks
- Architectural features
- Exterior or interior installations
- Swimming or feature pools

FEATURES

- 3-sided illumination spreads light over wider area
- UV & flame resistant
- Suitable for use around salt or chlorinated water



LED WATTS 13W/m

INPUT VOLTS 24V DC Constant Voltage

OPERATING TEMP. -25°C ~ +50°C

MAX. RUN PER POWER FEED 10m using one feed
20m using two feeds

BEAM ANGLE 210°

LED TYPE Epistar SMD LED 5050

LED QTY 72 LED/m

SOURCE LIFE 50,000 hours

WARRANTY 5 years

DIMENSIONS W16.5 x H16.5mm

BEND DIRECTION Vertical bending

CUTTING LENGTH 83.3mm

MINIMUM BEND RADIUS 60mm

HOUSING UV & flame resistant white PVC

INGRESS PROTECTION IP67 Snap Connector or IP68 Injection Moulding
Protection established by use of connection type


CONTROL Requires 3-channel controller

MOUNTING Profile and clips available


NEON Y3 | 13W/M | RGB | CONNECTION DIAGRAMS

FG (Green)
ACL (Brown)
AC/N (Blue)

① Regular Connection



② PWM Control



③ DMX Control

