




NEON ARC | TUNEABLE WHITE



COLOUR	CODE
--------	------

TUNEABLE 2500K - 5000K	BL-LS-4825
---------------------------	------------

ELECTRICAL & OPTICAL DATA VARIANCE +/- 10%
SOLD BY THE METRE



TECHNICAL DATA

LED WATTS	12 W/m	BEAM ANGLE	160°	CUTTING LENGTH	83.3 mm
INPUT VOLTS	24 V DC constant voltage	SOURCE LIFE	50,000 hrs	HOUSING	UV and flame resistant white PVC
OPERATING TEMP	- 20 °C ~ + 45 °C	WARRANTY	5 years	CONTROL	Requires 2-channel controller
LUMENS	WW ≥ 180 lm/m CW ≥ 180 lm/m	MIN BEND RADIUS	150 mm	MAX. RUN PER FEED	10 m using one feed 20 m using both feeds
CRI	≥ 80	BEND DIRECTION	Vertical bending	MOUNTING	See Installation Guide for mounting accessories
COLOUR	WW 2460 K +/-120K CW 5000 K +/-285K	DIMENSIONS	16 mm x 17 mm		
		INGRESS PROTECTION	IP67 or IP68 Protection established by use of connection type See Installation Guide for connections		

APPLICATION

- Ideal for applications where colour temperature adjustment is required
- Theatres, bars, restaurants and retail
- Cove lighting
- Architectural features
- Exterior or interior installations
- Swimming or feature pools

FEATURES

- Neon Arc can be curved in the opposite direction of the other Neon products
- UV and flame resistant
- Suitable for use around salt or chlorinated water